

Product Specification Sheet

VIBE® - Aircare Dispenser (US)



MODEL	VIBE®			
DESCRIPTION	AIRCARE DISPENSER			
CATEGORY	AIRCARE			
CODE(S)	VIBE-WW: VIBE DISPENSER W/W VIBE-WC: VIBE DISPENSER W/C VIBE-BB: VIBE DISPENSER BLACK-BLACK VIBE-BC: VIBE DISPENSER B/C			
BAR CODE No's.	VIBE-WW	X6	847583003192	10847583003199
		X24	847583003239	10847583003236
	VIBE-WC	X6	847583003208	10847583003205
		X24	847583003246	10847583003243
	VIBE-BB	X6	847583003215	10847583003212
		X24	847583003253	10847583003250
	VIBE-BC	X6	847583003222	10847583003229
		X24	847583003260	10847583003267

Product Description	VIBE® is an aircare dispenser that utilizes our patented & patent pending dispenser & refill technology, including our patented Vibrating Mesh Technology (VMT). The dispenser produces highly effective & consistent fragrance performance from start to finish.			
Feature(s) and Benefit(s)	<ul style="list-style-type: none"> ▪ Unlike heavier aerosol droplets which fall within minutes, the VMT micro particles are much smaller and lighter, remaining airborne for many hours. ▪ Pure fragrance oil is delivered in reliable and precise quantities using vibrating mesh technology. A mesh or membrane with 2,000 laser cut holes vibrates producing a mist of fine fragrance micro particles. ▪ VIBE® is environmentally safe. The fragrance formulation is VOC exempt & contains no propellants or HFCs. (*VOC regulations in the US and Canada <u>only</u>). ▪ It delivers superior fragrance for up to 90 days, covering a space of up to 510m³ / 18,000ft³. ▪ One VIBE® cartridge can replace up to three high volume metered aerosol cans or up to six passive fragrance refills. 			
Colour Option(s)	White-White / White-Chrome / Black-Chrome			
Material(s)	POM + PP			
Dispenser Dimensions (H x W x D)	mm	230 x 109 x 82	inches	9.1 x 4.3 x 3.2
x1 Carton Dimensions (L x W x H)	mm	117 x 87 x 236	inches	4.6 x 3.43 x 9.3
Gross Weight (Approx.)	kg	0.6	lb	1.3

Packing Specification(s)	Individual Carton / x6 Inner Carton / x24 Outer Carton			
x6 Carton Dimensions (L x W x H)	mm	265 x 240 x 242	inches	10.4 x 9.4 x 9.5
x6 Gross Weight (Approx.)	kg	3.9	lb	8.61
x24 Carton Dimensions (L x W x H)	mm	547 x 493 x 262	inches	21.5 x 19.4 x 10.3
x24 Gross Weight (Approx.)	kg	16.5	lb	36.4
Minimum Order Quantity	1			
Coverage	Effective in room sizes up to 510m ³			
Warranty	1 year guarantee against defects in parts & workmanship			
Pallet Quantity	Road & Sea = 28 cases (672 units) Air = 16 cases (384 units)			
Approval(s)	<ul style="list-style-type: none"> ▪ CE & FCC ▪ REACH SVHC < 0.1% (w/w). ▪ RoHS Directive 2011/65/EU ▪ FCC 47 CFR Part 15, Subpart B: 2014 ▪ EMC Directive 2004/108/EC ▪ EN 61000-6-1:2007 ▪ EN 61000-6-3:2007+A1:2011 ▪ EN 61000-3-2:2014 ▪ EN 61000-3-3:2013 			
Operating Conditions	<ul style="list-style-type: none"> ▪ Battery(s): 4 x C-Cell Alkaline (not included). ▪ Battery Life: 6–24 months (depending on program setup (i.e. 30, 45, 60 or 90 days per cartridge). ▪ Mains input adapter: 6V DC 1-2 A (optional – not included). ▪ Ambient Operating temperature: 0°C to 50°C (32°F - 122°F). ▪ Storage temperature: -10°C to 60°C (14°F - 140°F). ▪ Operating Temperatures of most batteries: 0°C to 50°C (32°F - 122°F). 			

Note:

- Features, specifications are subject to change without notification.
- *VOC regulations in the US and Canada only. The products are air fresheners and contain nothing defined as a VOC that is not a fragrance component and therefore the general exemption for air fresheners of 94510.F applies. Section 94510.F applies to the product from the US federal “Consumer Products Regulation”. The formulations are “pure fragrance” or “fragrance-only”. Note there are currently no restrictions on VOC content in Europe and what chemicals etc. would be classified as VOC exempt.

Product Specification Sheet

VIBE® - Fragrance Cartridge (US)



MODEL	VIBE® CARTRIDGE
DESCRIPTION	FRAGRANCE CARTRIDGE
CATEGORY	AIRCARE
CODE(S)	VIBE-RED: VIBE REFILL - APPLE ORCHARD VIBE-YELLOW: VIBE REFILL - CITRUS MANGO VIBE-BLUE: VIBE REFILL - COOL MINT VIBE-GREEN: VIBE REFILL - CUCUMBER MELON VIBE-WHITE: VIBE REFILL - OCEAN SPRAY

BAR CODE		RETAIL	WAREHOUSE
No's.	VIBE-RED	X4	847583004151
		X24	847583004205
	VIBE-YELLOW	X4	847583004168
		X24	847583004212
	VIBE-GREEN	X4	847583004182
		X24	847583004236
	VIBE-WHITE	X4	847583004199
		X24	847583004243

Product Description	VIBE® Refills utilize our patented & patent pending technology. All fragrances are complex, long lasting and offer unique fragrances for a variety of locations.			
Feature(s) and Benefit(s)	<ul style="list-style-type: none"> Highly effective at ultra low concentrations. *VOC exempt in the US and Canada <u>only</u>. Non-hazardous for all transportation. Environmentally friendly. Small and light particle size for optimum fragrance dispersal. Remains airborne for many hours without leaving surface deposits. 			
Refill Dimensions (H x W x D)	mm	106 x 53 x 44	inches	4.2 x 2.1 x 1.7
Gross Weight (Approx.)	kg	0.170	lb	0.37
Packing Specification(s)	x4 Inner Carton / x24 Outer Carton			
x4 Carton Dimensions (L x W x H)	mm	130 x 130 x 110	inches	5.12 x 5.12 x 4.33
x4 Gross Weight (Approx.)	kg	0.8	lb	1.8
x24 Carton Dimensions (L x W x H)	mm	264 x 134 x 334	inches	10.4 x 5.3 x 13.1
x24 Gross Weight (Approx.)	kg	5.0	lb	11.0
Material	POM			
Coverage area	m³	≤510	Ft³	≤18000
Refill size	ml	100		
Fragrance longevity	Up to 90 days			
Capacity	3000 metered sprays per fragrance refill			

Shelf life	24 months.
Minimum Order Quantity	1 case (4 refills).
Pallet Quantity	Road, Sea & Airfreight = 84 Cases (504 sale cases / 2016 units)
Compliance	<ul style="list-style-type: none">▪ Globally Harmonized System (GHS) for classification and labelling.▪ WHMIS 2015 (Workplace hazardous materials information system).▪ U.S. Occupational Safety and Health Administration (OSHA).▪ Regulation (EC) No 453/2010 (REACH)▪ Class 11A 100% - IFRA 47th Amendment / published June 2013).▪ Non-Hazardous for all transportation.
Operating Conditions	<ul style="list-style-type: none">▪ Operating temperature between 5°C and 50°C (41°F - 122°F)▪ Indoor use only. Dry and well-ventilated area.
Storage Conditions	<ul style="list-style-type: none">▪ Storage temperature between 5°C to 50°C (41°F - 122°F)▪ Cool, dry and well-ventilated area.

Note:

- Features, specifications are subject to change without notification.
- *VOC regulations in the US and Canada only. The products are air fresheners and contain nothing defined as a VOC that is not a fragrance component and therefore the general exemption for air fresheners of 94510.F applies. Section 94510.F applies to the product from the US federal "Consumer Products Regulation". The formulations are "pure fragrance" or "fragrance-only". Note there are currently no restrictions on VOC content in Europe and what chemicals etc. would be classified as VOC exempt.

Product Specification Sheet

VIBE® PLUS - Aircare Dispenser (US)



MODEL	VIBE® PLUS			
DESCRIPTION	AIRCARE DISPENSER			
CATEGORY	AIRCARE			
CODE(S)	VIBE-PLUS-W: VIBE PLUS DISPENSER W VIBE-PLUS-WC: VIBE PLUS DISPENSER W/C VIBE-PLUS-BC: VIBE PLUS DISPENSER B/C			
BAR CODE No's.			RETAIL	WAREHOUSE
	VIBE-PLUS-W	X1	847583005080	10847583005087
		X4	847583005127	10847583005124
	VIBE-PLUSWC	X1	847583005103	10847583005100
		X4	847583005141	10847583005148
	VIBE-PLUS-BC	X1	847583005110	10847583005117
		X4	847583005158	10847583005155

Product Description	VIBE® PLUS is an aircare dispenser that utilizes our patented & patent pending dispenser & refill technology, including our patented Vibrating Mesh Technology (VMT). The dispenser produces highly effective & consistent fragrance performance from start to finish.
Feature(s) and Benefit(s)	<ul style="list-style-type: none"> ▪ Unlike heavier aerosol droplets which fall within minutes, the VMT micro particles are much smaller and lighter, remaining airborne for many hours. ▪ Pure fragrance oil is delivered in reliable and precise quantities using vibrating mesh technology. A mesh or membrane with 3,000 laser cut holes vibrates, producing a mist of fine fragrance micro particles. ▪ Two spray heads & cartridges enable the unit to deliver a variety of fragrance blends from one dispenser (Optional HVAC kit available on request). ▪ Complete program flexibility allows tailored fragrance performance for all installation conditions. ▪ Each dispenser comes complete with a remote control for easy single or multiple simultaneous dispenser programming (1-3 channels) from up to 10m distance. ▪ VIBE® PLUS is environmentally safe. The fragrance formulation is VOC exempt & contains no propellants or HFCs. (*VOC regulations in the US and Canada only). ▪ It delivers superior fragrance for up to 180 days, covering a space of up to 3,400m³ / 120,000ft³.
Colour Option(s)	White / White-Chrome / Black-Chrome
Material(s)	POM + PP

Dispenser Dimensions (H x W x D)	mm	347 x 212 x 154	inches	13.7 x 8.3 x 6.1
x1 Carton Dimensions (L x W x H)	mm	221 x 171 x 374	inches	8.7 x 6.7 x 14.7
Gross Weight (Approx.)	kg	2.29	lb	5.05
Packing Specification(s)	Individual Carton / x4 Inner Carton			
x4 Carton Dimensions (L x W x H)	mm	464 x 355 x 390	inches	18.3 x 14 x 15.4
x4 Gross Weight (Approx.)	kg	10.08	lb	22.22
Minimum Order Quantity	1			
Coverage	Effective in room sizes up to 3,400m ³ / 120,000ft ³ .			
Warranty	1 year guarantee against defects in parts & workmanship			
Pallet Quantity	Road & Sea = 30 cases (120 units) Air = 18 cases (72 units)			
Approval(s)	<ul style="list-style-type: none"> ▪ CE & FCC ▪ REACH SVHC < 0.1% (w/w). ▪ RoHS Directive 2011/65/EU ▪ FCC 47 CFR Part 15, Subpart B: 2014 ▪ EMC Directive 2004/108/EC ▪ EN 61000-6-1:2007 ▪ EN 61000-6-3:2007+A1:2011 ▪ EN 61000-3-2:2014 ▪ EN 61000-3-3:2013 			
Operating Conditions	<ul style="list-style-type: none"> ▪ Battery(s): 4 x D-Cell Alkaline (not included). ▪ Battery Life: 6–24 months (depending on program setup). ▪ Mains input adapter: 6V DC 1.5-2 A (optional – not included). ▪ Ambient Operating temperature: 0°C to 40°C. ▪ Storage temperature: -10°C to 60°C. ▪ Operating Temperatures of most batteries: 0°C to 50°C. 			

- Note:
- Features, specifications are subject to change without notification.
 - *VOC regulations in the US and Canada only. The products are air fresheners and contain nothing defined as a VOC that is not a fragrance component and therefore the general exemption for air fresheners of 94510.F applies. Section 94510.F applies to the product from the US federal "Consumer Products Regulation". The formulations are "pure fragrance" or "fragrance-only". Note there are currently no restrictions on VOC content in Europe and what chemicals etc. would be classified as VOC exempt.

Product Specification Sheet

VIBE® & VIBE® PLUS 6V DC Power Adaptor



Vectair Model	VIBE/VIBE PLUS POWER ADAPTOR
Description	6V DC POWER ADAPTOR
Product Category	AIRCARE
Product Code	VIBE-ADAPTOR
Bar Code No.	X50 CASE: 5060060071797

Product Description	6V DC 1500mA Regulated Switchmode Power Supply to be used with the VIBE® & VIBE® PLUS dispensers.		
Feature(s) and Benefit(s)	<ul style="list-style-type: none"> ■ Operational Input Voltage 100-240V~, 50-60 Hz, 0.4A ■ Wall Plug-in, Regulated Switchmode AC-DC ■ 1.5 Metre Output Lead with 2.1mm DC Power Plug (Positive Polarity). ■ Input connector kit - US/UK/Europe/Australia interchangeable AC blades. 		
Type:	Wall Plug-in		
Technology	Regulated Switchmode AC-DC		
Critical Dimensions (L x W x H)	mm	64.5 x 38 x 35	inches 2.5 x 1.5 x 1.4
Weight (Approx.)	kg	0.164	lb 0.36
Packing Specification(s)	Individual Carton / x50 outer carton		
x1 Case Dimensions (L x W x H)	mm	135 x 61 x 55	inches 5.3 x 2.4 x 2.2
x1 Gross Weight (Approx.)	kg	0.182	lb 0.40
x50 Case Dimensions (L x W x H)	mm	TBC	inches TBC
x50 Gross Weight (Approx.)	kg	9.5	lb 20.9
Colour Option(s)	Black		
Material(s)	ABS Moulded Plastic		
Packing Specification(s)	White Carton		
Minimum Order Quantity	1		
Safety Approval(s)	<ul style="list-style-type: none"> ■ RoHS / WEEE ■ CE/ TÜV / FCC / UL <p>EN55022:2010/AC:2011 EN61000-3-2:2014 EN 61000-3-3:2013 EN55024:2010 IEC61000-4-2:2008 IEC61000-4-3:2006/AI:2007/A2:2010 IEC61000-4-4:2012 IEC61000-4-5:2014 IEC61000-4-5:2014 IEC61000-4-6:2013 IEC61000-4-8 :2009 IEC61000-4-11 :2004 EMI Standard: FCC PART 15 Class B UL 60950-1, 2nd Edition,2014-10-14 CSA C22.2 N0.60950-1-07, 2nd Edition,2014-10</p>		

	EN60950-1 :2006+A1 1 +A1 +A12+A2 BS EN60950-1 :2006+A2 AS/NZS 60950.1:2015
Operating Conditions	<ul style="list-style-type: none">■ (AC) Rated Input 100-240V■ (DC) Power Output: 6V■ Watts: 9.0■ Output Current: 1500mA (1.5A)■ Frequency Rated: 50-60Hz■ Indoor Use Only■ Storage Temperature: -20°C ~ +70°C■ Operating Temperature: 0° C ~ +40° C■ Operating Humidity: 10% ~ 95%

Note: Features, specifications are subject to change without notification.